

TECHNICAL SHEET

**PRODUCT: APPLIES FOR ALL PRODUCTS PORCELAIN SIZE CM.
30X30 UPON NORM UNE-EN-ISO 10545**

- DRY PRESS CERAMIC TILES GLAZED
- WORK SIZE IN MM: $300 \times 300 \pm 0,6\%$
- WORK SIZE THICKNESS IN MM: $8.0 \pm 5\%$
- STRAIGHTNESS DEVIATION INSIDE THE NORM
- WATER ABSORPTION: 0,28%
- SURFACE ABRASION: CLASS 4
- HOUSEHOLD CHEMICALS: GA
- SWIMMING POOL SALTS: GA
- ACIDS AND ALKALIS (LOW CONCENTRATIONS): GLA
- ACIDS AND ALKALIS (HIGH CONCENTRATIONS): GHA
- STAINS HAVING TRACING ACTIONS: CLASS 5
- STAINS HAVING CHEMICAL OXIDIZING ACTION: CLASS 5
- STAINS HAVING FILMING ACTIONS: CLASS 5
- MOSH HARDNESS: 5
- SLIP RESISTANCE CLASS: R-10, CLASS 2.
- GROUP BIa STANDARD UNE - EN 14411

Onda, 01-09-25